



**SPRING CLAMPS** These are the handiest of all clamps. They are quick to apply and hold firmly. Widely used for holding parts while glue dries, keeping roll goods from unrolling, holding straight edges in place, and many other holding jobs. Fast and easy to use. Vinyl-cushioned tips and grips. Three sizes meet almost every need.

Cat. No.	SC-1M,	1" Opening,	4" Long,	Weight	3 oz,	10 pcs/box,	100 pcs/ctn
Cat. No.	SC-2M,	2" Opening,	6" Long,	Weight	6 oz,	10 pcs/box,	100 pcs/ctn
Cat. No.	SC-3M,	3" Opening,	9" Long,	Weight	14 oz,	5 pcs/box,	30 pcs/ctn



**VACUUM CUP CLAMP SET** With 4 5/8" cups, it holds together almost all rigid smooth nonporous panels for seaming. Popular for joining solid surface panels and laminated flooring panels. It has an aluminum bracket that can be gripped by a variety of clamping devices including spring clamps and strap clamps. It has a very positive locking lever which also provides quick and easy release.

Cat. No. VC-SET, Two Cups & One 2" Spring Clamp      Single Cup Cat. No. VC-1



**SANDING BELTS** High quality American made belts in the most popular sizes and grits. Cloth is X-weight fabric with resin bonded Aluminum Oxide. Open coat resists clogging. Taped diagonal butt joint runs in either direction without thumping. The best belt for wood. Packed 10/box, 50/ctn. Approx. weight 2 lb/box.

ALL THESE SIZES	IN ALL THESE GRITS
3 x 21, 3 x 24, 4 x 24	#40, 50, 60, 80, 100, 120
Cat. No. SB-(size)(grit),	Example: SB-32140 is 3" x 21", #40 grit



**SANDING BELT & DISC CLEANER** Most belts and discs are discarded because they are clogged, not worn out. When held firmly (and carefully) against a running belt or disc, this rubberized substance removes the gummy clogging and restores the cutting ability. Abrasive life is extended many times, and downtime to change belt or disc is also reduced. Not to be used on wide belts or conveyor-type sanders. Industrial size is about 30% larger than standard belt cleaners.

Cat. No. BC-228, Size: 2" x 2" x 8", Wt 15 oz, 25/ctn



**REINFORCED FILAMENT TAPES** A high density of filaments makes these tapes almost impossible to break. Very aggressive high-tack pressure sensitive adhesives provide a quick grip and high holding power. Perfect for securing carpet rolls, bundling moldings or heavy parts, for banding cartons, and taping cabinet doors shut for shipping.

3M Brand Type 8934 Cat. No. TR-893418, 3/4" x 60 yd roll, 48/ctn, Wt 17 lb  
 INTERTAPE Brand Cat. No. FT-4001, 1" x 60 yd roll, 36/ctn, Wt 17 lb

Other widths of both **FILAMENT** and **MASKING** tapes are available special order.

**3M Brand MASKING TAPE** A top quality general purpose masking tape. Used for paint masking, surface protection, temporary labeling, bundling light materials, and taping cabinet doors closed. 3M type 2214.

Cat. No. MT-221418, 3/4" x 60 yd roll, 48/ctn, Wt 14 lb      Cat. No. MT-221424, 1" x 60 yd roll, 36/ctn, Wt 14 lb



**GORILLA TAPE** This is not ordinary DUCT Tape. With a double adhesive layer, strong reinforced backing, and all weather shell, this 2" wide tape is super strong and it resists harsh conditions. POPULAR SCIENCE Best of 2006 List.

Cat. No. GT-12, 12 yard rolls, 16 roll counter display, Wt 10 lb  
 Cat. No. GT-35, 35 yard rolls, 12 roll counter display, Wt 20 lb



**BENCH BRUSH** Keep work areas free of sawdust and chips that can contaminate fresh glue surfaces and applicators and that can mar finished surfaces. Also used for final dusting of finished tops, cabinets, and other products prior to final polishing and delivery. Static-free natural horsehair bristles do the most thorough and gentle job. Bristles are 2 1/2" long, overall length is 12". Cat. No. BR-8H, Wt 10 oz, 12 pcs/box



**TEMPILAQ** Temperature indicating paint-on material works on either side of the laminate. Using the brush in the cap, apply a stroke at the location to be formed. In a few seconds the solvent evaporates (provide ventilation), then it's ready for heating, then forming when the coating changes appearance.

**TEMPILSTIK** Temperature indicating crayons guide you in establishing a heat-up cycle for laminate forming. Just stroke a mark on the sheet at the location to be heated and formed. TEMPILSTIK works best when applied to the rougher back surface of the laminate sheet. Not for decorative side.

Each TEMPILAQ or TEMPILSTIK indicates a specific temperature. At the rated temperature, the signal is the onset of a glassy or waxy appearance that occurs, not a change in color. Can be used directly on dried contact adhesive. Catalog number indicates the temperature in degrees Fahrenheit.

TEMPILAQ in 2 oz bottles: Cat. Nos. TL-300, TL-313, TL-325, TL-350  
 TEMPILSTIKS: Cat. Nos. TS-300, TS-313, TS-325, TS-350, 10 sticks/box  
 TEMPILAQ THINNER 2 oz bottle: Cat. No. TL-THIN