Practical Products Co. Woodworking, Laminate, Solid Surface, & Flooring Hand & Power Tools









BENCH BRUSH Keep work areas free of sawdust and chips that can contaminate fresh glue surfaces and applicators and that can mar finished surfaces. Also used for final dusting of finished tops, cabinets, and other products prior to final polishing and delivery. Static-free natural horsehair bristles do the most thorough and gentle job. Bristles are 2 1/2" long, overall length is 12". Cat. No. BR-8H, Wt 10 oz, 12 pcs/box

J-ROLLER Handiest roller of all. The 3" rubber roller is soft enough to avoid marring but firm enough to smooth out all covering materials, and is conductive enough to prevent static build up. Up to 50 lb per square inch can be applied to assure thorough bonding of the adhesive layer. Since there are no axle protrusions on the open end, you can roll close to uprights without danger of marring. Light weight with Comfort Grip handle, it is easy to use and to carry. Cat. No. JR-78C, Length 13", Wt 10 oz, 24/ctn

CURVED FRAME J-ROLLER This heftier version J-Roller is 14 1/2" long. The curved steel frame provides left-hand clearance and permits the application of greater pressure which water-based contact adhesives usually require. Two heavy non-slip vinyl hand grips provide firm control. Grips DO NOT SLIP.

Cat. No. JR-300, Length 15", Wt 1.5 lb, 12/ctn

EXTENSION ROLLER Three 2 1/4" resilient rollers let you cover a lot of territory in a hurry, be it decorative laminate, vinyl, or other adhesive-applied coverings. A favorite for decorative laminates, carpet, floor tile, and other resilient coverings. With the preferred loop handle grip at the roller section, heavy pressure can be applied right where it is needed - at the rollers. The twist-lock handle quickly adjusts from 18" to 27".

Cat. No. ER-333, Closed Length 18", Wt 3 lb Cat. No. ER-333RP, Replacement 3-Roller Set with Axle




SEAM ROLLERS These steel rollers apply leveling pressure to seams in decorative laminates, resilient flooring, and carpet so that the edges are pressed evenly and firmly in place. This provides the best seam appearance and assures bonding to prevent future lifting of edges. Also can be used to roll out blisters or air pockets. They have 9" hardwood handles, except SE-348S and SE-349S which have 6" handles. The bearing-mounted rollers are plated for stain and rust resistance and to prevent marring of surfaces. Open ended for close areas.

Cat. No. SE-348,	Both Edges Square,	Handle Length 9", Overall Length	12",	Wt 2 ¼ lb
Cat. No. SE-349R,	One Round Edge,	Handle Length 9", Overall Length	12",	Wt 2 ¼ lb
Cat. No. SE-348S,	Both Edges Square,	Handle Length 6", Overall Length	9",	Wt 2 lb
Cat. No. SE-349S,	One Round Edge,	Handle Length 6", Overall Length	9".	Wt 2lb



SQUEEZE ROLLER This lever action roller puts pressure on laminate edges to seal them down tight to the substrate. Very useful for correcting the occasional edge-lift problem. The tip roller rides on the underside and the mid roller rides on the upper side to put handle pressure on the edge. The rollers are non-marring firm plastic.

Cat. No. SR-79, Length 12", Wt 10 oz



Cat. No. RO-075, 75 lb Weight, 4 1/2" Dia., 16" Wide, 38" Length Cat. No. RO-076, 100 lb Weight, 5 1/2" Dia., 16" Wide, 38" Length

Cat. No.RO-074, Replacement Roller Wheeled Case, Wt 8 lb



